

Application

- ✓ Wiring harness for regions with extended temperature.
- ✓ Single cable wiring for car body or regions with moderate temperatures.
- ✓ Using copper alloy with high values will lead to an excellent signal cable for low-current applications, for example for switches and sensors.

Features


- ✓ Flame retardant
- ✓ Highly resistant against acids, lyes, petrol and diesel.
- ✓ Extra flexibility.
- ✓ Light weight
- ✓ Excellent resistance to oil and flame.
- ✓ RoHS.

Product Construction

- ✓ Conductor : Bare half hard copper (Cu ETP1).
- ✓ Insulation : Plasticized PVC (Reduced wall thickness).
- ✓ Colour : As per customer order.
- ✓ Conductor twist direction : S.

 Automotive Cables **YAH**

2D View



Technical Data

- ✓ Temperature Range : -40°C to 105°C / 3000h
- ✓ Voltage : 60V.
- ✓ Y : PVC
- ✓ A : Structure A.
- ✓ H : Half hard copper.

ISO 9001	ISO 14001	IATF 16949	AS 9100	ISO 45001	IRIS [™] Certification
IAS INTERNATIONAL ASSOCIATION SERVICE	LAB CO	ARAI [®] Progress through Research	REACH	RoHS	CE

Part Number	Conductor Construction				Insulation Wall Thickness Min.	Cable			Max. Conductor Resistance at 20°C	Current Carrying Capacity at Ambient temperature 40°C	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire Max.	Conductor Diameter Max.		Core Diameter		Weight Approx.			
						Min.	Max.				
	mm²	nos.	mm	mm	mm	mm	mm	kg/km	Ω/km	Amps	mtrs
D30102XX	0.22	7	0.21	0.70	0.20	1.10	1.20	3	84.8	8	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



Siechem Wires & Cables Meet EU RoHS Directive

www.siechem.com