



Siechem AERO 55 600 V Single Core insulated Statistical Process Controlled Airframe Wires

AERO 55

Application

- ✓ Hook up signal wire & cables used in aircraft, avionics, military electronics, satellites, helicopters, missiles, automobiles and appliances.

Features

- ✓ Insulation does not shrink in hostile working environment .
- ✓ Better cut though resistance characteristics
- ✓ Single or dual wall constructions.
- ✓ Small size and light weight.
- ✓ No melting or dripping due to prolonging excess heat because of EBXL process.
- ✓ Resistance to soldering iron & over load.
- ✓ Excellent chemical resistance to many acids, carbon solvents, fuels, lubricants, missile fuels, oxidizers etc.
- ✓ Temperature rating -65°C to + 200°C [-85°F to +392°F], stable installed performance in very hot, extremely cold and high vacuum conditions
- ✓ Outstanding electrical arc tracking resistance in wet and dry conditions.
- ✓ Very low toxic.
- ✓ Mechanical ruggedness.
- ✓ Good flexibility.
- ✓ Excellent scrape abrasion.
- ✓ RoHS Compliant.

Product Construction

- ✓ Conductor : Annealed Tinned Copper Conductor (Optional : Silver Coated Copper Conductor / Nickel Coated Copper Conductor)
- ✓ Insulation : Radiation Cross-Linked Specially Formulated ETFE (Ethylene Tetrafluoroethylene)
- ✓ Single core
- ✓ Colour : As Per Customer Order.

Technical Data

- ✓ Temperature Rating
 - i) Tin Plated Conductor : -65°C to + 150°C
 - ii) Silver or Nickel Plated Conductor : -65°C to + 200°C
- ✓ Voltage Rating : 600V, Medium weight
- ✓ Scrape Abrasion : >100 cycles
- ✓ Flexing Endurance : >1000 cycles
- ✓ Shrinkage : < 1 %
- ✓ Thermal Endurance : 200°C, 10000h
- ✓ Permittivity at 1KHz : 2.7
- ✓ Dissipation Factor : 0.001

Standards

- ✓ SAE AS227759/32-35 and / 41 to / 46
- ✓ NEMA-WC-27500(Cables)
- ✓ Def-Stan 61-12 Part 33 Issue 5
- ✓ VDE 9426, 9427, 9428
- ✓ British Standard 3G233
- ✓ Boeing BMS 13-48
- ✓ Airbus ABS 0820 to 0826
- ✓ ASTM D150

ISO 9001	ISO 14001	OHSAS 18001	AS 9001	ISO 45001			CE
----------	-----------	-------------	---------	-----------	--	--	----

Part Number	Wire Size (AWG)	Cross Section Area (Sq.mm)	No.of Strands (Nos.)	Diameter of Single Wire (Nom.) (mm)	Overall Diameter (Nom.) (mm)	Cable Weight (Approx.) (kg/km)
55P21085XXYY	26	0.13	19	0.10	0.10	2.05
55P21084XXYY	24	0.20	19	0.13	1.02	2.95
55P21083XXYY	22	0.33	19	0.16	1.17	4.31
55P21082XXYY	20	0.52	19	0.20	1.39	6.51
55P21081XXYY	18	0.82	19	0.25	1.63	9.81
55P21080XXYY	16	1.31	19	0.29	1.82	12.46
55P21079XXYY	14	2.08	19	0.36	2.20	19.17
55P21078XXYY	12	3.31	37	0.32	2.68	29.36
55P21077XXYY	10	5.26	37	0.40	3.29	46.31

Note : XX* & YY* : Please add last two digits in the part number as per the colour code given hereunder replacing XX & YY while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
----------	-------------	-----------	------------	------------	-----------	------------	------------	-------------	-------------



Siechem Wires & Cables Meet EU RoHS Directive

Lead Free	Hg Free	Cd Free	Cr ⁶⁺ Free	PBB Free	PBDE Free
-----------	---------	---------	-----------------------	----------	-----------

www.siechem.com