

Siechem 5P3-30B, 127 Ohm
Application

- ✓ Capacitances design, Suitable for any kind of mobile radios use.
- ✓ Low loss transmission

Product Construction


- ✓ Conductor : Annealed Plain Solid Copper
Conductor as per IS 8130
- ✓ Insulation : Cellular PE as per BS 6234
- ✓ Colour : White
- ✓ Braiding : APC as per IS 8130
- ✓ Outersheath : PVC ST2 as per IS 5831
- ✓ Sheath Colour : As per Customer order

Technical Data

- ✓ Rated Temperature : + 60°C
- ✓ Characteristic Impedance : 127Ω at 1MHz
- ✓ Electrostatic Capacity : 30 pF/ m at 1KHz
- ✓ High Temperature Exposure Test : 80°C
- ✓ Attenuation Factor : 90 dB/km at 10 MHz (Max)

Features

- ✓ Low loss.
- ✓ Low Capacitance.

2D View

**Automotive
Cables**
5P3-30B

ISO 9001	ISO 14001	IATF 16949	AS 9100	ISO 45001	IRIS [™] Certification

Part Number	Conductor Construction			Insulation Wall Thickness Nom.	Braiding Wire dia Nom.	Thickness of Sheath (Nom)	Overall Diameter Nom.	Max. Conductor Resistance	Weight Approx.
	Nominal Cross-Section	No. of Strands	Diameter of Wire (Nom)						
	AWG	Nos.	mm	mm	mm	mm	mm	Ω/km	kg/km
A502A1609XX*	29	1	0.29	1.4	0.1	0.5	5.0 ± 0.2	271	32

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	


Siechem Wires & Cables Meet EU RoHS Directive
www.siechem.com