



Application

- ✓ Wire harness of low-tension electric circuits for automobiles.
- ✓ Used in motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.
- ✓ Especially used for circuits requiring heat resistance.

Features

- ✓ Flame retardant
- ✓ Highly resistant against acids, lyes, petrol and diesel.
- ✓ Flexible conductor with Electron beam cross linked polyethylene super thin wall insulation for smaller diameter and lesser weight.
- ✓ Heat resistant.

Product Construction

- ✓ Conductor : Soft-annealed electrolytic copper E-Cu ETP1 according to JIS C 3102, bare conductor construction according to JASO D 608 (Reference)
- ✓ Insulation : Electron beam cross linked Polyethylene
- ✓ Colour : As per customer order.
- ✓ Single core

**Automotive
Cables**

AESSX

Technical Data

- ✓ Temperature Range :
- 40°C to +120°C (3000 Hours)
- ✓ Standard : JASO D 608 (Reference)
- ✓ Test Voltage : 1 kV
- ✓ A : Low tension cables for automobiles
- ✓ E : Polyethylene insulated
- ✓ SS : Very Thin wall type
- ✓ X : Cross linked


ISO 9001	ISO 14001	IATF 16949	AS 9100	ISO 45001	IRIS TM Certification

Part Number	Conductor Construction				Insulation Wall Thickness Nom.	Cable			Max. Conductor Resistance at 20°C	Current Carrying Capacity	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire max.	Conductor Diameter Approx.		Overall Diameter		Weight Approx.			
						Nom.	Max.				
	mm ²	nos.	mm	mm	mm	mm	mm	kg/km	Ω/km	Amps	mtrs
81554XX*	0.85	19	0.24	1.2	0.3	1.8	1.9	10	21.7	20	1000
81504XX	0.3	7	0.26	0.8	0.3	1.4	1.5	5	50.2	12	500
81506XX	0.5	7	0.32	1.0	0.3	1.6	1.7	7	32.7	16	500
81512XX	1.25	19	0.29	1.5	0.3	2.1	2.2	4	14.9	26	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ * Other length as per Customer order.
- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 120°C and ambient air temperature of 40°C.



Siechem Wires & Cables Meet EU RoHS Directive

www.siechem.com