



Application

- ✓ Wire harness of low-tension electric circuits for automobiles.
- ✓ Used in motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.

Product Construction

- ✓ Conductor : Soft-annealed electrolytic copper E-Cu ETP1 according to JIS C 3102, bare conductor construction according to JASO D 611
- ✓ Insulation : PVC,
- ✓ Colour : As per customer order.
- ✓ Single core

Technical Data

- ✓ Temperature Range : - 40°C to +80°C (3000 Hours)
- ✓ Standard : JASO D 611
- ✓ Test Voltage : 1 kV
- ✓ A : Low tension cables for automobiles
- ✓ V : Vinyl insulated
- ✓ SS : Very Thin type
- ✓ f : Extra flexible Conductor

Features

- ✓ Flame retardant.
- ✓ Highly resistant against acids, lyes, petrol and diesel.
- ✓ Extra flexible conductor with PVC very thin wall insulation for smaller diameter and lesser weight.
- ✓ Excellent flexibility.

Automotive Cables AVSS f


ISO 9001	ISO 14001	IATF 16949	OHSAS 18001	IRIS TM Certification
LABCO	ARAI [®] Progress through Research	REACH COMPLIANT	RoHS COMPLIANT	CE

Part Number	Conductor Construction				Insulation Wall Thickness Nom.	Cable		Max. Conductor Resistance at 20°C	Current Carrying Capacity	Standard Length*	
	Nominal Cross-Section	No. of Strands	Diameter of Single wire max.	Conductor Diameter Approx		Overall Diameter					Weight Approx.
						Nom	Max.				
	mm ²	nos.	mm	mm	mm	mm	mm	kg/km	Ω/km	Amps	mtrs
80604XX*	0.3	19	0.16	0.8	0.30	1.4	1.5	5	48.8	9	1000
80606XX	0.5	19	0.19	1.0	0.30	1.6	1.7	7	34.6	11	1000
80608XX	0.75	19	0.23	1.2	0.30	1.8	1.9	9	23.6	14	1000
80612XX	1.25	37	0.21	1.5	0.30	2.1	2.2	14	14.6	19	1000
80614XX	2	37	0.26	1.8	0.40	2.6	2.7	22	9.50	26	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ * Other length as per Customer order.
- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 80°C and ambient air temperature of 40°C.



Siechem Wires & Cables Meet EU RoHS Directive

Lead Free	Hg Free	Cd Free	Cr ⁶⁺ Free	PBB Free	PBDE Free
-----------	---------	---------	-----------------------	----------	-----------

www.siechem.com