



**Application**

- ✓ Low-tension electric wire for automobiles.
- ✓ Used in motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.

**Product Construction**

- ✓ Conductor : Soft-annealed electrolytic Copper E-Cu ETP1 according to DIN 13602, bare conductor
- ✓ Insulation : PP-FR (Polypropylene FR) Low halogen
- ✓ Colour : As per customer order.
- ✓ Single core

**Technical Data**

- ✓ Temperature Range : - 40°C to +125°C (3000 Hours)
- ✓ Test Voltage: 3kV (r.m.s.) for cables < 0.5 mm<sup>2</sup> 5kV (r.m.s.) for cables ≥ 0.5 mm<sup>2</sup>
- ✓ Standed : Ford ES-AU5T- 1A348  
FIAT 91107/17  
Renault 36-05-009-N.  
VW 60306-1

**Features**

- ✓ Flame retardant
- ✓ Highly resistant against acids, lyes, petrol and diesel.
- ✓ Flexible conductors with PP Thin wall insulation with increased mechanical strength.
- ✓ Extra flexibility.

**Automotive Cables Auto 125 P**

<b>ISO 9001</b>	<b>ISO 14001</b>	<b>IATF 16949</b>	<b>OHSAS 18001</b>	<b>IRIS™ Certification</b>
<b>LABCO</b>	<b>ARAI®</b> <small>Progress through Research</small>	<b>REACH</b> <small>COMPLIANT</small>	<b>RoHS</b> <small>COMPLIANT</small>	<b>CE</b>


Part Number	Conductor Construction				Insulation Wall Thickness Nom.	Cable		Current Carrying Capacity	Max. Conductor Resistance at 20°C	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire max.	Conductor Diameter Nom.		Overall Diameter Max.	Weight Approx.			
	mm <sup>2</sup>	nos.	mm	mm	mm	mm	kg/km	Amps	Ω/km	mtrs
84105XX*	0.35	7	0.26	0.8	0.20	1.3	5	11	54.4	500
84106XX	0.5	19	0.19	1.0	0.22	1.6	7	15	37.1	500
84108XX	0.75	24	0.21	1.2	0.24	1.9	9	19	24.7	500
84110XX	1	32	0.21	1.35	0.24	2.1	13	23	18.5	500
84113XX	1.5	30	0.26	1.7	0.24	2.4	17	30	12.7	500
84114XX	2	28	0.31	2.0	0.28	2.8	22	37	9.42	500
84116XX	2.5	50	0.26	2.2	0.28	3.0	27	42	7.6	500
84117XX	3	45	0.31	2.4	0.32	3.4	34	48	6.15	500
84119XX	4	56	0.31	2.75	0.32	3.7	43	57	4.71	500
84123XX	6	84	0.31	3.3	0.32	4.3	63	74	3.14	500
84127XX	10	80	0.41	4.5	0.48	5.8	112	116	1.82	500
84128XX	16	126	0.41	5.5	0.52	7.0	172	146	1.16	500

Note : XX\* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

✓ Current Carrying capacity given is for the maximum conductor operating of 125° C and ambient air temperature of 40°C.

✓ \* Other length as per Customer order.



**Siechem Wires & Cables Meet EU RoHS Directive**

<b>Lead Free</b>	<b>Hg Free</b>	<b>Cd Free</b>	<b>Cr<sup>6+</sup> Free</b>	<b>PBB Free</b>	<b>PBDE Free</b>
------------------	----------------	----------------	-----------------------------	-----------------	------------------

www.siechem.com