



Application

- ✓ Low-tension electric wire for Automobiles.
- ✓ Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.

Product Construction

- ✓ Conductor : Soft-annealed electrolytic Copper E-Cu ETP1 according to DIN 13602, bare conductor
- ✓ Insulation : TPE- E (Thermoplastic Polyester Elastomer)
- ✓ Colour : As per customer order.
- ✓ Single core

Technical Data

- ✓ Temperature Range :
- 40°C to +150°C (3000 Hours)
- ✓ Test Voltage: 3kV (r.m.s.) for cables < 0.5 mm²
5kV (r.m.s.) for cables ≥ 0.5 mm²
- ✓ FL : Automotive cable
- ✓ R : Reduced wall thickness
- ✓ 12Y : Thermoplastic Polyester Elastomer
- ✓ A : Symmetrical
- ✓ Standard : ISO 6722, Class D

Features

- ✓ Flame retardant
- ✓ Highly resistant against acids, lyes, Petrol and diesel.
- ✓ Excellent mechanical properties
- ✓ Fuel resistance
- ✓ Excellent thermal stability

**Automotive
Cables**

FLR12Y - A

ISO 9001	ISO 14001	IATF 16949	AS 9100	ISO 45001	IRIS TM Certification

Part Number	Conductor Construction				Insulation Wall Thickness Min.	Cable		Current Carrying Capacity	Max. Conductor Resistance at 20°C	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire max.	Conductor Diameter Nom.		Overall Diameter Max.	Weight Approx.			
	mm ²	nos.	mm	mm	mm	mm	kg/km	Amps	Ω/km	mtrs
A89302XX*	0.22	7	0.20	0.6	0.20	1.2	3	10	84.8	500
A89305XX	0.35	7	0.26	0.80	0.20	1.3	5	11	54.4	500
A89306XX	0.5	19	0.19	1.00	0.22	1.6	6	14	37.1	500
A89308XX	0.75	19	0.23	1.20	0.24	1.9	9	18	24.7	500
A89310XX	1	19	0.26	1.35	0.24	2.1	11	22	18.5	500
A89313XX	1.5	19	0.32	1.70	0.24	2.4	16	28	12.7	500
A89316XX	2.5	19	0.41	2.20	0.28	3.0	26	40	7.6	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 150°C and ambient air temperature of 40°C.
- ✓ * Other length as per Customer order.



Siechem Wires & Cables Meet EU RoHS Directive

www.siechem.com