



Siechem 3 Round Core APC Conductor EBXL - XLPE 120°C Insulated GI wire Armoured PVC Sheathed 600/1000 V Power cable as per BS 5467

Application

- ✓ Transmission and distribution of Power Industrial units
- ✓ Commercial and residential places
- ✓ Indoor and outdoor uses
- ✓ Cable ducts, cable trays conduits Direct burial and underground burial where mechanical damage risk for cables.

Product Construction

- ✓ Conductor : Annealed Plain copper conductor complying with BS 6360
- ✓ Insulation : Electron Beam Cross Linked Polyethylene 120°C
- ✓ Armour : GI wire
- ✓ Jacket : PVC Complying with BS 6746

Technical Data

- ✓ Operating Temperature : -15°C to +120°C High Insulation resistance at elevated temperature
- ✓ Short Circuit Temperature : 280°C
- ✓ Bending radius (min) : 12 x Cable dia
- ✓ Rated Voltage : 600/1000 V
- ✓ Test Voltage : 3.5 kV for 5 mins.
- ✓ Specification : BS 5467

Features

- ✓ Electron Beam Cross Linked.
- ✓ Enhanced Mechanical, Electrical, Thermal & Weathering properties.
- ✓ Soldering iron resistant
- ✓ Resistance to corona effect.
- ✓ Easy jointing & termination
- ✓ Better resistance to most chemicals & acids
- ✓ Low direct electric losses.
- ✓ High current carrying capacity.

IS : 7098 (Pt.1) CML-6819184	ISO 9001	ISO 14001	OHSAS 18001
AS 9100	ISO 45001		

Part Number	Area	Cond.Min. No.of Wires	Thickness of EBXL / XLPE Insulation (Nom.)	Dimension of Arm Wire	Thickness of Outer Sheath	Approx Overall diameter	Approx.Net Wt.of Cable	Max.D.C Resistance at 20 deg.C	Current Rating For EBXL -XLPE Cables (125°C)			Current Rating For Chemically Cured XLPE Cables (90°C)			Short Circuit Rating for 1 sec
									Direct in Ground	In Duct	In Air	Direct in Ground	In Duct	In Air	
	Sq.mm	Nos	mm	mm	mm	mm	Kg/Km	Ω/KM	Cu	Cu	Cu	Cu	Cu	Cu	Cu
750ER1303	1.5	1	0.6	0.9	1.24	13.3	335	12.1	33	30	29	25	23	22	0.21
750ER1603	2.5	1	0.7	0.9	1.24	14.6	408	7.41	44	40	39	34	31	30	0.36
750ER1903	4	1	0.7	0.9	1.24	15.6	488	4.61	57	52	52	44	40	40	0.57
750ER2303	6	1	0.7	0.9	1.24	16.7	583	3.08	72	65	65	55	50	51	0.86
750ER2703	10	7	0.7	1.25	1.4	20.5	914	1.83	95	86	82	73	66	63	1.4
750ER2803	16	7	0.7	1.25	1.4	20.5	1071	1.15	126	113	117	97	87	90	2.3
750ER3003	25	7	0.9	1.6	1.4	24.8	1627	0.727	159	143	143	122	110	110	3.6
750ER3203	35	19	0.9	1.6	1.4	24.8	1888	0.524	190	170	182	146	131	140	5.0

Cable conforming to IEC 60502 & VDE-0271 also available according to customer requirement.



www.siechem.com