



Application

- ✓ Low-tension electric wire for automobiles.
- ✓ Used in motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.

Product Construction

- ✓ Conductor : Soft-annealed electrolytic Copper E-Cu ETP1 according to DIN 13602, bare conductor
- ✓ Insulation : PP-FR (Polypropylene FR) Low halogen
- ✓ Colour : As per customer order.
- ✓ Single core

Technical Data

- ✓ Temperature Range :
- 40°C to +125°C (3000 Hours)
- ✓ Test Voltage: 3kV (r.m.s.) for cables < 0.5 mm²
5kV (r.m.s.) for cables ≥ 0.5 mm²
- ✓ Standard : Ford ES-AU5T- 1A348
FIAT 91107/17
Renault 36-05-009-N.
VW 60306-1

Features

- ✓ Flame retardant
- ✓ Highly resistant against acids, lyes, petrol and diesel.
- ✓ Flexible conductors with PP Thin wall insulation with increased mechanical strength.
- ✓ Extra flexibility.

**Automotive
Cables**
Auto 125 P

ISO 9001	ISO 14001	IATF 16949	OHSAS 18001	AS 9100	ISO 45001


Part Number	Conductor Construction				Insulation Wall Thickness Nom.	Cable		Current Carrying Capacity	Max. Conductor Resistance at 20°C	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire max.	Conductor Diameter Nom.		Overall Diameter Max.	Weight Approx.			
	mm ²	nos.	mm	mm	mm	mm	kg/km	Amps	Ω/km	mtrs
84105XX*	0.35	7	0.26	0.8	0.20	1.3	5	11	54.4	500
84106XX	0.5	19	0.19	1.0	0.22	1.6	7	15	37.1	500
84108XX	0.75	24	0.21	1.2	0.24	1.9	9	19	24.7	500
84110XX	1	32	0.21	1.35	0.24	2.1	13	23	18.5	500
84113XX	1.5	30	0.26	1.7	0.24	2.4	17	30	12.7	500
84114XX	2	28	0.31	2.0	0.28	2.8	22	37	9.42	500
84116XX	2.5	50	0.26	2.2	0.28	3.0	27	42	7.6	500
84117XX	3	45	0.31	2.4	0.32	3.4	34	48	6.15	500
84119XX	4	56	0.31	2.75	0.32	3.7	43	57	4.71	500
84123XX	6	84	0.31	3.3	0.32	4.3	63	74	3.14	500
84127XX	10	80	0.41	4.5	0.48	5.8	112	116	1.82	500
84128XX	16	126	0.41	5.5	0.52	7.0	172	146	1.16	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ Current Carrying capacity given is for the maximum conductor operating of 125° C and ambient air temperature of 40°C.

- ✓ * Other length as per Customer order.


Siechem Wires & Cables Meet EU RoHS Directive

Lead Free	Hg Free	Cd Free	Cr ⁶⁺ Free	PBB Free	PBDE Free
-----------	---------	---------	-----------------------	----------	-----------

www.siechem.com