

Siechem EMD/40036046 ATC, 125°C Diesel Electric Locomotive Cables

Application


- Thin walled flexible EBXL cables for tap changer of Electric Locomotives.
- ✓ For Diesel Electric Locomotive Cables.

Features

- ✓ Excellent resistance to high and low temperature
- ✓ Outstanding flame retardant
- ✓ Halogen free
- ✓ Excellent flexibility
- Resistance to Oil, Fuel, Ozone and Weathering.
- ✓ Easy to strip
- ✓ Low smoke density
- Soldering iron resistant
- ✓ Electron Beam Cross Linked.

Product Construction

- ✓ Conductor : Annealed Tinned Copper Flexible Conductor.
- Insulation : Specially formulated Dual Layer, EBXL125°C.
- \checkmark Laid up : Cores are twisted.
- ✓ Colour : Yellow/White, Yellow/Black or as per Customer order.



Technical Data

(>10000 hrs @ +125°C).

Rated Voltage : 600 V AC Specification: EDPS 179 - 40036046

1

1

Temperature Range : -65°C to +125°C

Stochem EMD/2003d046 ATC/125/C Dicsol Electrical Location/Cables	5

EMD Part Number	Number of Cores and Conductor Size	Outer Diameter (Nom.)		Total Weight	
		mm	Inches	Kg/Km approx.	
40036046	2Cx18 AWG	5.44	0.214	33.30	



All information given are in good faith. Siechem's liability is only to replace the defective portion of cables provided the same is mutually established as manufacturing defects within the guarantee period as agreed in writing and Siechem shall not be liable for any compensation or damages. Siechem reserves the right to revise any of the above specifications without prior intimation. Subject to Chennai Jurisdiction.