

Application

- ✓ Used for conditioning compressors, PTC auxiliary heaters and the vehicle.
- ✓ Internal connection of the charging socket to the charger aggregate.
- ✓ Used today by different OEMs for the connection of HV aggregates.

Features

- ✓ High Flexibility
- ✓ High temperature resistance
- ✓ Low Mechanical loads

Product Construction


- ✓ Conductor : Annealed Tinned Flexible Copper Conductor (Asymmetrical, Structure C)
- ✓ Insulation : EVA (Thin wall)
- ✓ Inner Sheath : EBXL-XLPO
- ✓ Outer Sheath : EBXL-XLPO - Orange
- ✓ Colour : As Per Customer Order.
- ✓ Multi Core

Technical Data

- ✓ Voltage Rating : 600V AC / 1000V DC
- ✓ Temperature Range : - 40°C to +180°C (3000 Hours)
- ✓ Test Voltage :
 - i) Insulation : 6 kV for cables < 0.5 mm²
8 kV for cables ≥ 0.5 mm²
 - ii) Outer Jacket : 8 kV for all cables
- ✓ FHL : Automotive Cable (High Voltage)
- ✓ R : Reduced wall thickness
- ✓ 4G : EVA
- ✓ 13X : EBXL-XLPO
- ✓ C : Asymmetrical (Structure C)
- ✓ Standard : ISO 6722, Class E & LV 216-2

ISO 9001	ISO 14001	IATF 16949	OHSAS 18001	AS 9100	ISO 45001

2D View



Automotive Cables **FHLR4G13X - C**

Part Number	Conductor Construction				Insulation Thickness (Min.)	Core Diameter (Max.)	Thickness of Outer Sheath (Min.)	Cable		Max. Conductor Resistance at 20°C
	Nominal Cross-Section	No. of Strands	Diameter of Single wire (Max.)	Conductor Diameter (Max.)				Overall Diameter (Max.)	Weight Approx.	
	mm ²	nos.	mm	mm	mm	mm	mm	kg/km	Ω/km	
A7420602	2C X 0.5	26	0.16	1.10	0.22	1.60	0.35	4.6	27	38.2
A7420603	3C X 0.5	26	0.16	1.10	0.22	1.60	0.40	5.0	35	38.2
A7420604	4C X 0.5	26	0.16	1.10	0.22	1.60	0.40	5.4	40	38.2
A7420605	5C X 0.5	26	0.16	1.10	0.22	1.60	0.40	6.0	50	38.2
A7420802	2C X 0.75	38	0.16	1.30	0.22	1.90	0.50	5.4	40	25.4
A7420803	3C X 0.75	38	0.16	1.30	0.22	1.90	0.55	5.9	50	25.4
A7420804	4C X 0.75	38	0.16	1.30	0.22	1.90	0.55	6.4	60	25.4
A7420805	5C X 0.75	38	0.16	1.30	0.22	1.90	0.55	7.0	70	25.4
A7421002	2C X 1	54	0.16	1.50	0.22	2.10	0.60	6.0	50	19.1
A7421003	3C X 1	54	0.16	1.50	0.22	2.10	0.65	6.4	60	19.1
A7421004	4C X 1	54	0.16	1.50	0.22	2.10	0.65	7.0	75	19.1
A7421005	5C X 1	54	0.16	1.50	0.22	2.10	0.65	7.7	90	19.1
A7421302	2C X 1.5	76	0.16	1.70	0.22	2.40	0.76	6.6	70	13.0
A7421303	3C X 1.5	76	0.16	1.70	0.22	2.40	0.76	7.1	85	13.0
A7421304	4C X 1.5	76	0.16	1.70	0.22	2.40	0.76	7.8	102	13.0
A7421305	5C X 1.5	76	0.16	1.70	0.22	2.40	0.76	8.5	125	13.0
A7421602	2C X 2.5	140	0.16	2.20	0.24	3.00	0.76	8.0	100	7.82
A7421603	3C X 2.5	140	0.16	2.20	0.24	3.00	0.76	8.5	122	7.82
A7421604	4C X 2.5	140	0.16	2.20	0.24	3.00	0.76	9.5	160	7.82
A7421605	5C X 2.5	140	0.16	2.20	0.24	3.00	0.76	10.5	190	7.82
A7421902	2C X 4	224	0.16	2.80	0.28	3.70	0.76	9.7	150	4.85
A7421903	3C X 4	224	0.16	2.80	0.28	3.70	0.76	10.3	185	4.85
A7421904	4C X 4	224	0.16	2.80	0.28	3.70	0.80	11.3	235	4.85
A7421905	5C X 4	224	0.16	2.80	0.28	3.70	0.90	12.5	290	4.85
A7422302	2C X 6	320	0.16	3.40	0.28	4.30	0.90	11.0	210	3.23
A7422303	3C X 6	320	0.16	3.40	0.28	4.30	1.00	11.8	270	3.23
A7422304	4C X 6	320	0.16	3.40	0.28	4.30	1.00	13.0	340	3.23
A7422305	5C X 6	320	0.16	3.40	0.28	4.30	1.00	14.3	405	3.23

* Other length as per Customer order.



Siechem Wires & Cables Meet EU RoHS Directive

Lead Free	Hg Free	Cd Free	Cr ⁶⁺ Free	PBB Free	PBDE Free
-----------	---------	---------	-----------------------	----------	-----------

www.siechem.com