

Single Core High Conductivity Copper Conductor EM-5 Chlorinated Rubber Compound 85°C Sheathed Welding Cable as per DIN VDE 0282 Specification

Application

- ✓ For use between welding generator and the hand electrode and the work piece.
- ✓ For use in automobile industry, in ship building, in transport and conveyor systems, tool making machinery, welding robots, etc.

Product Construction




- ✓ Conductor : Fine stranded plain or tinned class-6 copper conductors conforming to DIN VDE 0295, IEC 60228 and HD 383
- ✓ Separator : Dry Paper, Polyester Tape
- ✓ Sheath : Neoprene outer jacket, chlorinated rubber compound Em5
- ✓ Colour : Orange or Black

Technical Data

- ✓ Temperature Range : 85°C
- ✓ Voltage for Testing : 1000 V AC
- ✓ Bending Radius(Minimum) : 6x Overall dia.

Features

- ✓ Flexibility under rough, open dry, damp conditions.
- ✓ Oli resistant to DIN EN 60811-2-1
- ✓ High flexibility under the effect of ozone, light oxygen, inert gas, oil or petrol.

| | | | | | | | |
|-----------------|------------------|--------------------|----------------|------------------|---|---|---|
| ISO 9001 | ISO 14001 | OHSAS 18001 | AS 9100 | ISO 45001 |  |  |  |
|-----------------|------------------|--------------------|----------------|------------------|---|---|---|

| Part Number | Nominal Conductor Area (mm ²) | Maximum Strand dia (mm) | Thickness of Insulation (mm) | Approx. Overall diameter (mm) | Approx Weight of Cable (kg/km) | Maximum Conductor Resistance at 20°C (Ω/Km) | |
|-------------|---|-------------------------|------------------------------|-------------------------------|--------------------------------|---|--------------|
| | | | | | | Plain Wires | Tinned Wires |
| 53827XX | 10 | 0.21 | 2.0 | 8.8 | 153 | 1.83 | 1.84 |
| 53828XX | 16 | 0.21 | 2.0 | 9.9 | 220 | 1.15 | 1.16 |
| 53830XX | 25 | 0.21 | 2.0 | 11.2 | 310 | 0.727 | 0.734 |
| 53832XX | 35 | 0.21 | 2.0 | 12.4 | 410 | 0.524 | 0.529 |
| 53834XX | 50 | 0.21 | 2.2 | 14.4 | 565 | 0.387 | 0.391 |
| 53837XX | 70 | 0.21 | 2.4 | 16.5 | 780 | 0.268 | 0.270 |
| 53838XX | 95 | 0.21 | 2.6 | 18.7 | 1040 | 0.193 | 0.195 |
| 53841XX | 120 | 0.51 | 2.8 | 20.6 | 1300 | 0.153 | 0.154 |
| 53842XX | 150 | 0.51 | 3.0 | 22.7 | 1600 | 0.124 | 0.126 |

Rating factors for variation in Ambient temperature

| Ambient Temperature °C | 25 | 30 | 35 | 40 | 45 | 50 |
|------------------------|------|------|------|------|------|------|
| Rating factor | 1.08 | 1.00 | 0.91 | 0.82 | 0.71 | 0.58 |

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

| | | | | | | | | | | |
|----------------|-------------|---------------|--------------|--------------|-------------------|---------------|--------------|-------------|-------------|-------------|
| Red - 01 | Yellow - 02 | Blue - 03 | Black - 04 | Green - 05 | Yellow-Green - 06 | Grey - 07 | Brown - 08 | White - 09 | Orange - 10 | Violet - 11 |
| Chocolate - 12 | Tan - 13 | Charcoal - 14 | LT Blue - 15 | DK Grey - 16 | LT Green - 17 | DK Green - 18 | DK Blue - 19 | Purple - 20 | Pink - 21 | |

- ✓ * Other length as per Customer order.
- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 80°C and ambient air temperature of 40°C.