

Siechem UL 3068 ATC Silicone Rubber Insulated and Fibre Glass Braided 150°C 300 Vac Cable

Application

- ✓ Internal wiring of meters, panels, electrical and electronic equipment.
- ✓ Appliance wiring

Product Construction

- ✓ Conductor : Annealed Tinned Solid / Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber
- ✓ Braiding : Fibre Glass Braid


Technical Data

- ✓ Operating Temperature : - 40°C to + 150°C
- ✓ Voltage : 300 Vac
- ✓ Test method : UL 758

Features

- ✓ Halogen free
- ✓ Flame retardant

2D View



	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A13387XX	30	1/0.255	0.381	1.7	361	3
A13386XX	28	1/0.321	0.381	1.8	227	4
A13385XX	26	1/0.407	0.381	1.9	143	5
A13484XX	24	7/0.193	0.381	2.0	94.2	6
A13483XX	22	7/0.255	0.381	2.2	59.4	7
A13482XX	20	10/0.255	0.381	2.4	37.2	9
A13481XX	18	16/0.255	0.381	2.6	23.4	13
A13480XX	16	26/0.255	0.381	2.9	14.7	18

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



www.siechem.com