

**Siechem UL 3069 ATC Silicone Rubber Insulated and Fibre Glass Braided 105°C 600 Vac Cable**

**Application**

- ✓ Internal wiring of meters, panels, electrical and electronic equipment.
- ✓ Appliance wiring

**Product Construction**

- ✓ Conductor : Annealed Tinned Solid / Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber
- ✓ Braiding : Fibre Glass Braid


**Technical Data**

- ✓ Operating Temperature : - 40°C to + 105°C
- ✓ Voltage : 600 Vac
- ✓ Test method : UL 758

**Features**

- ✓ Halogen free
- ✓ Flame retardant

**2D View**



	<b>ISO 9001</b>	<b>ISO 14001</b>	<b>OHSAS 18001</b>	<b>AS 9100</b>
<b>AS 45001</b>		<b>ALSTOM</b>		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A13585XX	26	1/0.41	0.762	2.8	143	9
A13784XX	24	7/0.193	0.762	3.0	94.2	11
A13783XX	22	7/0.255	0.762	3.2	59.4	13
A13782XX	20	10/0.255	0.762	3.3	37.2	15

Note : XX\* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



www.siechem.com