

**Siechem UL 3070 ATC Silicone Rubber Insulated and Fibre Glass Braided 150°C 600 Vac Cable**

**Application**

- ✓ Internal wiring of meters, panels, electrical and electronic equipment.
- ✓ Appliance wiring

**Product Construction**

- ✓ Conductor : Annealed Tinned Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber
- ✓ Braiding : Fibre Glass Braid


**Technical Data**

- ✓ Operating Temperature : - 40°C to + 150°C
- ✓ Voltage : 600 Vac
- ✓ Test method : UL 758

**Features**

- ✓ High temperature resistance
- ✓ RoHS Compliant
- ✓ Halogen free

**2D View**



	<b>ISO 9001</b>	<b>ISO 14001</b>	<b>OHSAS 18001</b>	<b>AS 9100</b>
<b>AS 45001</b>		<b>ALSTOM</b>		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A13981XX	18	16/0.255	0.762	3.6	23.4	19
A13980XX	16	26/0.255	0.762	3.9	14.7	25
A13979XX	14	41/0.255	0.762	4.3	9.2	34
A13978XX	12	65/0.255	0.762	4.8	5.82	47

Note : XX\* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



www.siechem.com