

Siechem UL 3074 ATC Silicone Rubber Insulated and Fibre Glass Braided 200°C 600 Vac Cable
Application

- ✓ Internal wiring of meters, panels, electrical and electronic equipment.
- ✓ Appliance wiring

Product Construction


- ✓ Conductor : Annealed Tinned Solid / Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber
- ✓ Braiding : Fibre Glass Braid

Technical Data

- ✓ Operating Temperature : - 40°C to + 200°C
- ✓ Voltage : 600 Vac
- ✓ Test method : UL 758

Features

- ✓ High temperature resistance
- ✓ RoHS Compliant
- ✓ Halogen free

2D View


	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A17278XX	12	65/0.254	0.762	4.8	5.82	47
A17078XX	12	1/2.053	0.762	4.8	5.53	47

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	


www.siechem.com