

**Siechem UL 3101 ATC Silicone Rubber Insulated and Fibre Glass Braided 150°C 600 Vac Cable**

**Application**

- ✓ Internal wiring of electric clothes, dryers where exposed to temperatures not exceeding 150 deg C or internal wiring of appliances where exposed to temperatures not exceeding 150 deg C

**Product Construction**

- ✓ Conductor : Annealed Tinned Solid / Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber
- ✓ Braiding : Fibre Glass Braid


**Technical Data**

- ✓ Operating Temperature : - 40°C to + 150°C
- ✓ Voltage : 600 Vac
- ✓ Test method : UL 758

**Features**

- ✓ RoHS compliant
- ✓ High temperature resistant
- ✓ Halogen free

**2D View**



	<b>ISO 9001</b>	<b>ISO 14001</b>	<b>OHSAS 18001</b>	<b>AS 9100</b>
<b>AS 45001</b>				

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A17877XX	10	1/2.589	1.14	6.1	3.476	76
A17977XX	10	105/0.255	1.14	6.2	3.66	77

Note : XX\* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



www.siechem.com