

Siechem UL 3132 ATC Silicone Rubber Insulated 150°C 300 Vac Cable
Application

- ✓ Internal wiring where totally enclosed.
- ✓ Appliance wiring

Product Construction


- ✓ Conductor : Annealed Tinned Copper Solid / Stranded Conductor
- ✓ Insulation : Silicone Rubber
- ✓ Braiding : Fibre Glass Braid (Optional)

Technical Data

- ✓ Operating Temperature : - 40°C to + 150°C
- ✓ Voltage : 300 Vac
- ✓ Test method : UL 758

Features

- ✓ RoHS compliant
- ✓ High temperature resistance
- ✓ Halogen free

2D View


	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A18687XX	30	1/0.255	0.38	1.2	361	2
A18686XX	28	1/0.321	0.38	1.3	227	2
A18685XX	26	1/0.407	0.38	1.4	143	3
A18784XX	24	7/0.202	0.38	1.5	94.2	4
A18783XX	22	7/0.255	0.38	1.7	59.4	6
A18782XX	20	10/0.255	0.38	1.9	37.2	7
A18781XX	18	16/0.255	0.38	2.1	23.4	11

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	


www.siechem.com