

**Siechem UL 3143 ATC Silicone Rubber Insulated 200°C 600 Vac Cable**

**Application**

- ✓ Internal wiring of appliances Where totally enclosed.

**Product Construction**

- ✓ Conductor : Annealed Tinned Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber


**Technical Data**

- ✓ Operating Temperature : - 60°C to + 200°C
- ✓ Voltage : 600 Vac
- ✓ Test method : UL 758

**Features**

- ✓ Halogen free
- ✓ Flame retardant
- ✓ Oil resistant
- ✓ Low temperature resistant
- ✓ Resistance to ozone, chemical oil and fuel

**2D View**



	<b>ISO 9001</b>	<b>ISO 14001</b>	<b>OHSAS 18001</b>	<b>AS 9100</b>
<b>AS 45001</b>		<b>ALSTOM</b>		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A21181XX	18	7/0.386	1.57	4.9	23.2	30
A21180XX	16	7/0.488	1.57	5.2	14.6	37
A21179XX	14	7/0.615	1.57	5.6	8.96	47
A21178XX	12	19/0.470	1.57	6.1	5.75	61

Note : XX\* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



www.siechem.com