

Siechem UL 3213 ATC Silicone Rubber Insulated 150°C 600 Vac Cable
Application

- ✓ Internal wiring of meters, panels, electrical and electronic equipment
- ✓ Appliance wiring

Product Construction


- ✓ Conductor : Annealed Tinned Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber

Technical Data

- ✓ Operating Temperature : - 60°C to + 150°C
- ✓ Voltage : 600 Vac
- ✓ Test method : UL 758

Features

- ✓ Halogen free
- ✓ Flame retardant
- ✓ Oil resistant
- ✓ Low temperature resistant
- ✓ Resistance to ozone, chemical oil and fuel

2D View


	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A22376XX	8	168/0.254	1.14	6.5	2.35	104
A223A09XX	7	210/0.254	1.14	6.9	1.87	125
A22375XX	6	63/0.511	1.14	7.0	1.43	147
A223A08XX	5	84/0.511	1.14	8.1	1.13	190
A22374XX	4	105/0.511	1.14	8.7	0.900	231
A223A07XX	3	133/0.511	1.14	9.5	0.713	287
A22373XX	2	161/0.511	1.14	10.2	0.566	341

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	


www.siechem.com