

Siechem UL 3278 ATC Silicone Rubber Insulated and Fibre Glass Braided 150°C 600 Vac Cable

Application

- ✓ Internal wiring of appliances (such as heating appliances and lighting fixtures)

Product Construction

- ✓ Conductor : Annealed Tinned Copper Conductor
- ✓ Insulation : Silicone Rubber
- ✓ Braiding : Fibre Glass Braid


Technical Data

- ✓ Operating Temperature : - 60°C to + 150°C
- ✓ Rated Voltage : 600 Vac
- ✓ Test method : UL 758

Features

- ✓ Halogen free
- ✓ Flame retardant
- ✓ Oil resistant
- ✓ Low temperature resistant
- ✓ Resistance to ozone, chemical oil and fuel

2D View



	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A25976XX	8	168/0.254	1.52	7.9	2.35	126
A259A09XX	7	210/0.254	1.52	8.4	1.87	148
A25975XX	6	266/0.254	1.52	8.9	1.48	179
A259A08XX	5	133/0.40	1.52	9.4	1.16	211
A25974XX	4	133/0.45	1.52	10.2	0.918	261
A259A07XX	3	133/0.51	1.52	10.9	0.728	317
A25973XX	2	259/0.41	1.52	11.7	0.580	378
A25972XX	1	259/0.46	2.03	13.6	0.460	491
A25990XX	1/0	259/0.51	2.03	14.6	0.357	598
A25991XX	2/0	259/0.58	2.03	14.7	0.284	734
A25992XX	3/0	259/0.65	2.03	15.8	0.224	904
A25994XX	4/0	259/0.73	2.03	17.1	0.179	1115

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



www.siechem.com