

Siechem UL 3301 ATC Silicone Rubber Insulated and Fibre Glass Braided 150°C 600 Vac Cable

Application

- ✓ Internal wiring of meters, panels, electrical and electronic equipment
- ✓ Appliance wiring

Product Construction

- ✓ Conductor : Annealed Tinned Copper Conductor
- ✓ Insulation : Silicone Rubber
- ✓ Braiding : Fibre Glass Braid


Technical Data

- ✓ Operating Temperature : - 60°C to + 150°C
- ✓ Rated Voltage : 600 Vac
- ✓ Test method : UL 758

Features

- ✓ Halogen free
- ✓ Flame retardant
- ✓ Oil resistant
- ✓ Low temperature resistant
- ✓ Resistance to ozone, chemical oil and fuel

2D View



	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A26182XX	20	10/0.255	1.02	3.8	37.2	19
A26181XX	15	16/0.255	1.02	4.1	23.4	23
A26180XX	16	26/0.255	1.02	4.4	14.7	29
A26179XX	14	41/0.255	1.02	4.8	9.2	39
A26178XX	12	65/0.254	1.02	5.3	5.85	52
A26177XX	10	105/0.255	1.02	5.9	3.66	74
A261XXXX	9	133/0.254	1.02	6.3	2.96	89
A26176XX	8	168/0.254	1.02	6.7	2.35	108

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



www.siechem.com