

**Siechem UL 3322 ATC Silicone Rubber Insulated 200°C 600 Vac Cable**
**Application**

- ✓ Mercury switch leads, where protected against mechanical abuse

**Product Construction**


- ✓ Conductor : Annealed Tinned Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber

**Technical Data**

- ✓ Operating Temperature : - 60°C to + 200°C
- ✓ Voltage : 600 Vac
- ✓ Test method : UL 758

**Features**

- ✓ Halogen free
- ✓ Flame retardant
- ✓ Oil resistant
- ✓ Low temperature resistant
- ✓ Resistance to ozone, chemical oil and fuel

**2D View**


	<b>ISO 9001</b>	<b>ISO 14001</b>	<b>OHSAS 18001</b>	<b>AS 9100</b>
<b>AS 45001</b>		<b>ALSTOM</b>		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A26684XX	24	7/0.202	0.76	2.5	94.2	8
A26683XX	22	7/0.255	0.76	2.7	59.2	10
A26682XX	20	10/0.255	0.76	2.8	37.2	12
A26681XX	18	16/0.255	0.76	3.1	23.4	16
A26680XX	16	26/0.255	0.76	3.4	14.7	22

Note : XX\* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	


[www.siechem.com](http://www.siechem.com)