

Siechem UL 3367 ATC Silicone Rubber Insulated 200°C 300 Vac Cable
Application

- ✓ Internal wiring of appliances where totally enclosed

Product Construction


- ✓ Conductor : Annealed Tinned Solid / Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber

Technical Data

- ✓ Operating Temperature : - 60°C to + 200°C
- ✓ Voltage : 300 Vac
- ✓ Test method : UL 758

Features

- ✓ Halogen free
- ✓ Flame retardant
- ✓ Oil resistant
- ✓ Low temperature resistant
- ✓ Resistance to ozone, chemical oil and fuel

2D View


	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A26885XX	26	1/0.407	0.38	1.3	143	3
A26884XX	24	1/0.505	0.38	1.5	89.3	4
A26883XX	22	1/0.648	0.38	1.7	56.4	5
A26882XX	20	1/0.814	0.38	1.9	35.2	7
A26881XX	18	7/0.386	0.38	2.1	23.2	10
A26880XX	16	7/0.488	0.38	2.4	14.6	15
A26879XX	14	7/0.615	0.38	2.8	8.96	23
A26878XX	12	19/0.470	0.38	3.3	5.75	35
A26877XX	10	37/0.424	0.38	3.9	3.62	54

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	


www.siechem.com