

Siechem UL 3513 ATC Silicone Rubber Insulated and Fibre Glass Braided 200°C 600 Vac Cable
Application

- ✓ Internal wiring of electric clothes dryers.

Product Construction


- ✓ Conductor : Annealed Tinned Solid / Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber
- ✓ Braiding : Fibre Glass Braid

Technical Data

- ✓ Operating Temperature : - 60°C to + 200°C
- ✓ Voltage : 600 Vac
- ✓ Test method : UL 758

Features

- ✓ Halogen free
- ✓ Flame retardant
- ✓ Oil resistant
- ✓ Low temperature resistant
- ✓ Resistance to ozone, chemical oil and fuel

2D View


	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A27582XX	20	1/0.814	0.76	3.3	56.4	15
A27681XX	18	16/0.255	0.76	3.6	37.2	19
A27680XX	16	26/0.255	0.76	3.9	23.4	25
A27679XX	14	41/0.255	0.76	4.3	14.7	34
A27678XX	12	65/0.255	0.76	4.8	5.82	47
A27677XX	10	104/0.255	1.14	6.2	3.66	77
A27676XX	8	168/0.255	1.14	7.0	2.35	111
A27675XX	6	266/0.255	1.52	8.9	1.48	179
A27674XX	4	133/0.455	1.52	10.2	0.918	261
A27673XX	2	259/0.405	1.52	11.7	0.580	378
A27672XX	1	259/0.455	2.03	13.6	0.460	491
A27690XX	1/0	259/0.511	2.03	14.7	0.357	600
A27691XX	2/0	259/0.573	2.03	15.8	0.284	734
A27692XX	3/0	259/0.644	2.03	17.1	0.224	904
A27694XX	4/0	259/0.723	2.03	18.6	0.179	1115

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	


www.siechem.com