

Siechem UL 3530 ATC Silicone Rubber Insulated 150°C 600 Vac Cable
Application

- ✓ Internal wiring of appliances where totally enclosed

Product Construction


- ✓ Conductor : Annealed Tinned Copper Solid / Stranded Conductor
- ✓ Insulation : Silicone Rubber

Technical Data

- ✓ Operating Temperature : - 60°C to + 150°C
- ✓ Voltage : 600 Vac
- ✓ Test method : UL 758

Features

- ✓ Halogen free
- ✓ Flame retardant
- ✓ Oil resistant
- ✓ Low temperature resistant
- ✓ Resistance to ozone, chemical oil and fuel

2D View


	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A27985XX	26	1/0.407	0.76	2.8	143	9.5
A28084XX	24	7/0.193	0.76	3.0	94.2	11
A28083XX	22	7/0.255	0.76	3.2	59.4	13
A28082XX	20	10/0.255	0.76	3.3	37.2	15
A28081XX	18	16/0.255	0.76	3.6	23.4	19
A28080XX	16	26/0.255	0.76	3.9	14.7	25
A28079XX	14	41/0.255	0.76	4.3	9.2	34

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	


www.siechem.com