

Siechem UL 3566 ATC Silicone Rubber Insulated 150°C 600 Vac Cable

Application

- ✓ Internal wiring of appliances where not subjected to flexing or motion.

Product Construction

- ✓ Conductor : Annealed Tinned Copper Conductor
- ✓ Insulation : Silicone Rubber


Technical Data

- ✓ Operating Temperature : - 60°C to + 150°C
- ✓ Voltage : 600 Vac
- ✓ Test method : UL 758

Features

- ✓ Halogen free
- ✓ Flame retardant
- ✓ Oil resistant
- ✓ Low temperature resistant
- ✓ Resistance to ozone, chemical oil and fuel

2D View



	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A28681XX	18	16/0.254	1.14	3.8	23.4	21
A28680XX	16	26/0.254	1.14	4.1	14.7	27
A28679XX	14	41/0.254	1.14	4.5	9.2	36
A28678XX	12	65/0.254	1.14	5.0	5.82	49
A28677XX	10	104/0.254	1.14	5.7	3.66	71
A286XXXX	9	133/0.254	1.14	6.0	2.96	86
A28676XX	8	168/0.254	1.52	7.4	2.35	118
A286A09XX	7	210/0.254	1.52	7.9	1.87	139
A28675XX	6	266/0.254	1.52	8.4	1.48	170
A286A08XX	5	133/0.40	1.52	8.9	1.16	201
A28674XX	4	133/0.45	1.52	9.7	0.918	250

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



www.siechem.com