



Siechem UL 3580 ATC Silicone Rubber Insulated 150°C 1000 Vac Cable

Application

- ✓ As motor leads or internal wiring of appliances or electronic equipment where not subjected to mechanical abuse.

Product Construction

- ✓ Conductor : Annealed Tinned Solid / Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber


Technical Data

- ✓ Operating Temperature : - 60°C to + 150°C
- ✓ Voltage : 1000 Vac
- ✓ Test method : UL 758

Features

- ✓ Halogen free
- ✓ Flame retardant
- ✓ Oil resistant
- ✓ Low temperature resistant
- ✓ Resistance to ozone, chemical oil and fuel

2D View



	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A28785XX	26	1/0.407	1.14	2.8	143	9
A28884XX	24	7/0.193	1.14	3.1	94.2	11
A28883XX	22	7/0.255	1.14	3.2	59.4	13
A28882XX	20	10/0.255	1.14	3.4	37.2	15
A28881XX	18	16/0.255	1.14	3.6	23.4	19
A28880XX	16	26/0.255	1.14	3.9	14.7	26

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



www.siechem.com