

Siechem UL 3605 ATC Silicone Rubber Insulated and Fibre Glass Braided 150°C 600 Vac Cable

Application

- ✓ Internal wiring of meters, panels, electrical and electronic equipment
- ✓ Appliance wiring

Product Construction

- ✓ Conductor : Annealed Tinned Solid / Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber
- ✓ Braiding : Fibre Glass Braid


Technical Data

- ✓ Operating Temperature : - 60°C to + 150°C
- ✓ Voltage : 600 V
- ✓ Test method : UL 758

Features

- ✓ Halogen free
- ✓ Flame retardant
- ✓ Oil resistant
- ✓ Low temperature resistant
- ✓ Resistance to ozone, chemical oil and fuel

2D View



	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A29187XX	30	1/0.255	0.76	2.7	361	8
A29186XX	28	1/0.321	0.76	2.8	227	9
A29185XX	26	1/0.407	0.76	2.8	143	10
A29284XX	24	7/0.193	0.76	3.0	94.2	11

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



www.siechem.com