



Siechem UL 2128 APC, PVC Insulated 105°C, 600 V AC Cable

Application

- ✓ Appliance wiring
- ✓ Internal wiring of meters, panels, electrical and electronic equipment.

Features

- ✓ Flame retardant
- ✓ Resistant to water, oil, acids, solvents and fungus.

Product Construction

- ✓ Conductor : Annealed Solid / Stranded Bare Copper (Tinning on request)
- ✓ Insulation : PVC
- ✓ Optional Shield
- ✓ Jacket : PVC
- ✓ Colour : As per customer order.

Technical Data

- ✓ Temperature Range : +105°C
- ✓ Voltage Rating : 600 V AC

		ISO 9001	ISO 14001	AS 9100	ISO 45001

Part Number	Conductor Construction		Insulation Wall Thickness Nom.	Outer Sheath Thickness Nom.	Cable		Max. Conductor Resistance at 20°C
	Conductor Size	No. of Strands / Wire dia			Overall Diameter Max.	Weight Approx.	
	AWG	nos. / mm	mm	mm	mm	kg/km	Ω/km
4278403	24	7 / 0.193	0.8	0.8	7.04	67.73	87.6
4278303	22	7 / 0.254	0.8	0.8	7.39	78.89	55.4
4278203	20	10 / 0.254	0.8	0.8	7.72	88.35	34.8
4278103	18	16 / 0.254	0.8	0.8	8.25	105.46	21.8
4278003	16	26 / 0.254	0.8	0.8	8.96	131.21	13.7
4277803	12	19 / 0.47	0.8	0.61	9.23	312.33	5.43
4277803	12	19 / 0.47	0.8	0.61	10.91	357.10	5.43

