



Siechem UL 3288 APC, EBXL-XLPE Insulated 150°C, 600 V AC Cable

Application

- ✓ Appliance wiring
- ✓ Internal wiring of meters, panels, electrical and electronic equipment.

Product Construction

- ✓ Conductor : Annealed Solid / Stranded Bare Copper (Tinning on request)
- ✓ Insulation : EBXL-XLPE
- ✓ Colour : As per customer order.

Technical Data

- ✓ Temperature Range : +150°C
- ✓ Voltage Rating : 600 V AC

Features

- ✓ Flame retardant
- ✓ Resistant to water, oil, acids, solvents and fungus.



Part Number	Conductor Construction		Insulation Wall Thickness Nom.	Cable		Max. Conductor Resistance at 20°C
	Conductor Size	No. of Strands / Wire dia		Overall Diameter Max.	Weight Approx.	
	AWG	nos. / mm	mm	mm	kg/km	Ω/km
43584XX	24	7/0.193	0.76	2.16	6.74	87.6
43583XX	22	7/0.254	0.76	2.34	8.60	55.4
43582XX	20	10/0.254	0.76	2.50	10.52	34.8
43581XX	18	16/0.254	0.76	2.74	14.14	21.8
43580XX	16	26/0.254	0.76	3.07	19.89	13.7
43579XX	14	41/0.254	0.76	3.45	28.15	8.59
43578XX	12	65/0.254	0.76	3.94	40.95	5.41
43577XX	10	105/0.254	0.76	4.61	61.49	3.41
43576XX	8	168/0.254	1.15	6.21	103.38	2.18
43575XX	6	266/0.254	1.15	7.22	153.85	1.38
43574XX	4	133/0.45	1.15	8.51	233.24	0.865
S43581XX	18	1/1.024	0.76	2.58	13.51	21.4
S43580XX	16	1/1.291	0.76	2.85	18.74	13.5

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

