





Siechem Annealed Plain Copper Conductor 300/500V Rubber Insulated and Sheathed (H05BN4-F) Multicore Ordinary duty Cable

Application

- ✓ Use for medium mechanical stress in dry, damp and
 ✓ wet areas
- ✓ Handling equipment,In open air for agriculture plants
 ✓
- ✓ Installation on plaster, in temporary buildings and residential barracks
- ✓ Mobile power supplies, Worksites, stage and audio visual equipment
- ✓ Port areas and dams, use in drainage and water treatment
- ✓ Severe industrial environments like boilers, heating plates for transportable motors or machines at site.

Features

- ✓ Flame Retardant according to IEC/EN 60332-1-2
- ✓ High flexibility, Weather resistance, oil & grease resistant
- ✓ Capacity to withstand mechanical and thermal stresses
- ✓ In dry, damp and wet areas

Product Construction

- Conductor : Annealed Copper conductor, Class 5 flexible conductor EN 60228
- ✓ Optional : Tinned copper
- ✓ Insulation : Cross-linked elastomeric Compound
 Type EI 7 as per EN 50363-1
- ✓ Sheath : Cross-linked elastomeric Compound Type EM 7 as per EN 50363-2-1

O 01	 O 001	 S 00	1S 450	0)01
	_			



IS

90





Technical Data

✓ Specification :BS EN 50525-2-21:2011 BS-6500

- ✓ Test voltage : 2kv
- Conductor resistance : EN 60228
- ✓ Rated voltage : 300/500V(U₀/U)
- ✓ Max. Operating temperature :90°C

Dort Neurob an	Number		Conductor	Thickness of	Thickness of	Overall diameter		Max conductor	Weight
Part Number	of Cores	Size	diameter	insulation	Sheath	Minimum	Maximum	resistance at 20°C	approx. Kg/Km
		mm²	mm	mm	mm	mm	mm	Ω/km	Kg/Km
A0220802	2	0.75	1.14	0.6	0.8	5.7	7.4	26.0	66
A0221002	2	1	1.32	0.6	0.9	6.1	8.0	19.5	78
A0220803	3	0.75	1.14	0.8	0.9	6.2	8.1	26.0	81
A0221003	3	1	1.32	0.9	0.9	6.5	8.5	19.5	92

	Note: XX*: Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.									
Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	



www.siechem.com