



Siechem Annealed Plain Copper Conductor EVA Type Insulated and (HO5GGH2 -F) Flat Cables

Application

- ✓ Use for medium mechanical stress in dry, damp and wet areas
- ✓ Handling equipment, In open air for agriculture plants
- ✓ Installation on plaster, in temporary buildings and residential barracks
- ✓ Mobile power supplies, Worksites, stage and audio visual equipment
- ✓ Port areas and dams, use in drainage and water treatment
- ✓ Severe industrial environments like boilers, heating plates for transportable motors or machines at site.

Features

- ✓ Flame Retardant according to IEC/EN 60332-1-2
- ✓ High flexibility, Weather resistance, oil & grease resistant
- ✓ Capacity to withstand mechanical and thermal stresses
- ✓ In dry, damp and wet areas

Product Construction

- ✓ Conductor : Annealed Copper conductor, Class 5 flexible conductor EN 60228
- ✓ Optional : Tinned copper
- ✓ Insulation : Cross-linked elastomeric Compound Type EI 3 as per EN 50363-1
- ✓ Sheath : Cross-linked elastomeric Compound Type EM 4 as per EN 50363-2-1

Technical Data

- ✓ Specification : BS EN 50525-2-21:2011 BS-6500
- ✓ Test voltage : 2kV
- ✓ Conductor resistance : EN 60228
- ✓ Rated Voltage (u₀/u) : 300/500V
- ✓ Max. Operating temperature : 110°C

ISO 9001	ISO 14001	AS 9100	ISO 45001
---------------------	----------------------	--------------------	----------------------



Part Number	Number of Cores	Size	Conductor diameter	Thickness of insulation	Thickness of Sheath	Overall diameter (Height X Width)		Max Conductor resistance at 20°C	Weight approx.
						Minimum	Maximum		
		mm ²	mm	mm	mm	mm	mm	Ω/km	Kg/Km
A0280802	2	0.75	1.14	0.6	0.8	3.7 X 6.0	4.7 X 7.4	26.0	58

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

