



Application

- ✓ Wiring electrical equipment in trailers.
- ✓ Used in vehicles transporting hazardous goods.

Features

- ✓ Excellent UV resistance.
- ✓ Resistant to oils and Various chemicals.
- ✓ Resistant to cold

Product Construction

- ✓ Conductor: Finely Stranded Bare Copper Wires.
- ✓ Insulation: PVC Compound.
- ✓ Outer Sheath: Special PVC Compound.
- ✓ Colored Cores.

ISO 9001	ISO 14001	AS 9100	ISO 45001
---------------------	----------------------	--------------------	----------------------



Technical Data

- ✓ Temperature Range:
Fixed Installation : - 40°C to +85°C
- ✓ Testing Voltage : 5 kV
- ✓ Bending Radius(Minimum): 12 x Cable Diameter
- ✓ Rated Voltage:(U₀/U) 60 V
- ✓ Specific Insulation Resistance: 10 M Ohm x cm.
- ✓ As per VDE 0281

Part Number	Number of Cores and mm ² Per Conductor	Outer Diameter in mm approx.	Copper Index Kg/Km	Weight Kg/Km approx.
6201002A	2 X 1	6.4	19.2	64
6201002B	2 X 1	6.4	19.2	64
6201003C	3 X 1	6.4	28.8	71
6201003D	3 X 1	6.4	28.8	71
6201004E	4 X 1	6.4	38.4	79
620105H	5 X 1.5	6.4	48.0	86
6201302A	2 X 1.5	7.4	28.8	87
6201302B	2 X 1.5	7.4	28.8	87
6201304E	4 X 1.5	7.4	57.4	109

