



Application

- ✓ Used in battery cables.
- ✓ Commercial vehicles.

Features

- ✓ Polarity identification is possible without stripping the sheath or external marking.
- ✓ Double sheathed version is extremely tough.
- ✓ Very strong connection but offering easy separation of the cable by hand.

Product Construction

- ✓ Conductor : Finely Stranded Bare Copper Wires.
- ✓ Insulation : PVC based Compound.
- ✓ Outer Sheath : Special PVC Compound.
- ✓ Cores : Black with White Numbers.

ISO 9001	ISO 14001	AS 9100	ISO 45001
---------------------	----------------------	--------------------	----------------------



Technical Data

- ✓ Temperature Range : - 40°C to +85°C
- ✓ Testing Voltage : 3 kV
- ✓ Protective Conductor(PC) : G-With green/yellow PC
X-Without PC
- ✓ Bending Radius(Minimum) : 15 x Cable Diameter
- ✓ Rated Voltage : 75 V DC
- ✓ Specific Insulation Resistance : 10 M Ohm x cm.

Part Number	Number of Cores and mm ² Per Conductor	Outer Diameter in mm approx.	Copper Index Kg/Km	Weight Kg/Km approx.
6212302	2 X 6	15.2	120.0	231
6212702	2 X 10	17.8	200.0	553
6212802	2 X 16	20.0	308.0	793
6213002	2 X 25	24.2	480.0	1214
6213202	2 X 35	26.6	672.0	1632
6213402	2 X 50	31.3	960.0	2307
6213702	2 X 70	34.8	1350.0	3166

