



Siechem 3 Core Aluminium Conductor EBXL - XLPE 120°C Insulated GI strips Armoured PVC ST2 Sheathed 1100 V Power cable as per IS 7098

Application

- ✓ Transmission and distribution of Power Industrial units
- ✓ Commercial and residential places
- ✓ Indoor and outdoor uses
- ✓ Cable ducts, cable trays conduits
- ✓ Direct burial and underground burial where mechanical damage risk for cables.

Product Construction

- ✓ Conductor : Aluminium conductor complying with IS 8130
- ✓ Insulation : Electron Beam Cross Linked Polyethylene 120°C
- ✓ Armour : GI strips
- ✓ Jacket : PVC-ST2 (Optional : FRLS, ZHLS)

Technical Data

- ✓ Operating Temperature : -15°C to +120°C
- ✓ High Insulation resistance at elevated temperature
- ✓ Short Circuit Temperature : 280°C
- ✓ Bending radius (min) : 12 x Cable dia
- ✓ Rated Voltage : 1100 V
- ✓ Test Voltage : 3 kV for 5 mins.
- ✓ Specification : IS 7098

Features

- ✓ Electron Beam Cross Linked.
- ✓ Enhanced Mechanical, Electrical, Thermal & Weathering properties.
- ✓ Soldering iron resistant
- ✓ Resistance to corona effect.
- ✓ Easy jointing & termination
- ✓ Better resistance to most chemicals & acids
- ✓ Low direct electric losses.
- ✓ High current carrying capacity.

IS : 7098 (PL.1) CM/L-6819184	ISO 9001	ISO 14001	OHSAS 18001
AS 9100	ISO 45001		

Part Number	Area	Cond.Min. No.of Wires	Thickness of EBXL / XLPE Insulation (Nom.)	Dimension of Arm strips	Thickness of Outer Sheath	Approx Overall diameter	Approx.Net Wt.of Cable	Max.D.C Resistance at 20 deg.C	Current Rating For EBXL -XLPE Cables (125°C)			Current Rating For Chemically Cured XLPE Cables (90°C)			Short Circuit Rating for 1sec
									Direct in Ground	In Duct	In Air	Direct in Ground	In Duct	In Air	
	Sq.mm	Nos	mm	mm	mm	mm	Kg/Km	Ω/KM	Al	Al	Al	Al	Al	Al	Al
234WF2803	16	7	0.7	0.8X4	1.4	18.5	621	1.91	95	73	91	73	56	70	1.5
234WF3003	25	7	0.9	0.8X4	1.4	21.6	801	1.20	122	111	125	94	85	96	2.4
234WF3203	35	7	0.9	0.8X4	1.4	23.6	964	0.868	147	133	152	113	102	117	3.3
234WF3403	50	7	1.0	0.8X4	1.4	26.5	1189	0.641	173	156	185	133	120	142	4.7
234WF3703	70	19	1.1	0.8X4	1.56	29.8	1481	0.443	213	192	223	164	148	179	6.6
234WF3803	95	19	1.1	0.8X4	1.56	33.0	1826	0.320	255	229	287	196	176	221	9.0
234WF4103	120	19	1.2	0.8X4	1.56	36.1	2129	0.253	290	261	334	223	201	257	11.3
234WF4203	150	19	1.4	0.8X4	1.72	40.0	2598	0.206	324	291	380	249	224	292	14.2
234WF4403	185	37	1.6	0.8X4	1.72	44.0	3083	0.164	367	330	438	282	254	337	17.5
234WF4603	240	37	1.7	0.8X4	1.88	48.9	3758	0.125	424	381	519	326	293	399	22.6
234WF4803	300	37	1.8	0.8X4	2.04	53.8	4507	0.100	477	429	593	367	330	456	28.3
234WF4903	400	61	2.0	0.8X4	2.36	61.2	5800	0.0778	543	489	689	418	376	530	37.7

Cable conforming to IEC 60502 & VDE - 0271 also available according to customer requirement.



www.siechem.com