



Siechem 4 Core Round Aluminium Conductor EBXL - XLPE 120°C Insulated GI wire Armoured PVC ST2 Sheathed 1100 V Power cable as per IS 7098

Application

- ✓ Transmission and distribution of Power Industrial units
- ✓ Commercial and residential places
- ✓ Indoor and outdoor uses
- ✓ Cable ducts, cable trays conduits
- ✓ Direct burial and underground burial where mechanical damage risk for cables.

Product Construction

- ✓ Conductor : Aluminium conductor complying with IS 8130
- ✓ Insulation : Electron Beam Cross Linked Polyethylene 120°C
- ✓ Armour : GI wire
- ✓ Jacket : PVC-ST2 (Optional : FRLS, ZHLS)

Technical Data

- ✓ Operating Temperature : -15°C to +120°C
- ✓ High Insulation resistance at elevated temperature
- ✓ Short Circuit Temperature : 280°C
- ✓ Bending radius (min) : 12 x Cable dia
- ✓ Rated Voltage : 1100 V
- ✓ Test Voltage : 3 kV for 5 mins.
- ✓ Specification : IS 7098

Features

- ✓ Electron Beam Cross Linked.
- ✓ Enhanced Mechanical, Electrical, Thermal & Weathering properties.
- ✓ Soldering iron resistant
- ✓ Resistance to corona effect.
- ✓ Easy jointing & termination
- ✓ Better resistance to most chemicals & acids
- ✓ Low direct electric losses.
- ✓ High current carrying capacity.

IS : 7098 (Pl.1)  CM/L-6819184	ISO 9001	ISO 14001	OHSAS 18001
AS 9100	ISO 45001		

Part Number	Area	Cond.Min. No. of Wires	Thickness of EBXL / XLPE Insulation (Nom.)	Dimension of Arm Wire	Thickness of Outer Sheath	Approx Overall diameter	Approx.Net Wt. of Cable	Max.D.C Resistance at 20 deg.C	Current Rating For EBXL -XLPE Cables (125°C)			Current Rating For Chemically Cured XLPE Cables (90°C)			Short Circuit Rating for 1sec
									Direct in Ground	In Duct	In Air	Direct in Ground	In Duct	In Air	
	Sq.mm	Nos	mm	mm	mm	mm	Kg/Km	Ω/KM	Al	Al	Al	Al	Al	Al	Al
233ER1304	1.5	1	0.7	1.4	1.24	16.2	489	-	-	-	-	-	-	-	-
233ER1604	2.5	1	0.7	1.4	1.24	17.7	583	-	-	-	-	-	-	-	-
233ER1904	4	1	0.7	1.4	1.4	18.6	638	7.41	44	40	40	34	31	31	0.38
233ER2304	6	1	0.7	1.6	1.4	20.2	777	4.61	56	51	52	43	39	40	0.57
233ER2704	10	1	0.7	1.6	1.4	22.2	933	3.08	74	66	69	57	51	53	0.94

Cable conforming to IEC 60502 & VDE - 0271 also available according to customer requirement.

