

**Siechem SieCar 85-210 Coaxial Cable**

**Application**

- ✓ Wireless and antenna application
- ✓ Used for interior lines for monitoring system, CCTV feeder lines, wiring between the camera and control unit and video signal transmission.
- ✓ Automotive radio antennas
- ✓ Used for high-frequency signal transmission

**Product Construction**

- ✓ Conductor : Plain Copper Clad steel Conductor
- ✓ Insulation : PE
- ✓ Core Identification : Natural
- ✓ Braiding : ATC
- ✓ Sheath : PVC-Black

**Technical Data**


- ✓ Temperature : -40°C to + 85°C (3000 hrs)
- ✓ Max. Operating Voltage : 60V (DC)
- ✓ Nom. Capacitance 1 kHz : 73 pF/m
- ✓ Impedance : 75Ω

**Features**

- ✓ Supports High Bandwidth Levels
- ✓ Easy to Install
- ✓ Resistant to physical damage
- ✓ Less susceptible to noise interference compare to twisted pair.
- ✓ Highly resistant to EMI.
- ✓ Noise immunity due to a low error rate.

**Automotive Cables** **SieCar 85-210**

**2D View**



**Approvals | Accreditations | Certifications**



Part Number	Conductor Construction				Diameter Over Insulation (Nom)	Dia over Shielding (Nom)	Coverage of Shielding (Nom)	Overall Diameter (Nom)	Weight Approx.	Conductor Resistance at 20°C (Max)
	Area Cross Section	No. of Strands	Strand dia Nom.	Conductor Diameter (Nom)						
	Sq.mm	Nos.	mm	mm	mm	mm	%	mm	kg/km	Ω/km
C486020004	0.22	1	0.58	0.58	3.70	4.35	94	6.15	56.00	157.00

Note : XX\* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

\*\* We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.

Frequency (GHz)	0.1	0.2	0.5	0.8	1.0
Attenuation (dB/100m) at 20°C Nom.	12.4	17.9	29.3	37.9	42.9



www.siechem.com