

Siechem SieCar 90-508 Data Cable

Application

- ✓ Wireless and antenna application
- ✓ Used for interior lines for monitoring system, CCTV feeder lines, wiring between the camera and control unit and video signal transmission.
- ✓ Automotive radio antennas
- ✓ Used for high-frequency signal transmission

Features

- ✓ Supports High Bandwidth Levels
- ✓ Easy to Install
- ✓ Resistant to physical damage
- ✓ Less susceptible to noise interference compare to twisted pair.
- ✓ Highly resistant to EMI.
- ✓ Noise immunity due to a low error rate.

Product Construction


- ✓ Conductor : Annealed Plain Copper Conductor.
- ✓ Insulation : PE.
- ✓ Core Identification : Core Colour as per DIN 47100.
- ✓ Shielding : PETP - Al Mylar Tape.
- ✓ Braiding : ATC.
- ✓ Sheath : PVC - Black.

Technical Data

- ✓ Temperature : -40°C to + 90°C
- ✓ Max. Operating Voltage : 60V (DC)
- ✓ Characteristic Impedance : 100Ω

Automotive Cables SieCar 90-508

2D View



Approvals Accreditations Certifications



Part Number	Conductor Construction				Dia over Shielding (Nom)	Overall Diameter (Nom)	Weight Approx.	Conductor Resistance at 20°C (Max)
	No. of Wire x Size	No. of Strands	Strand dia Nom.	Conductor Diameter (Max)				
C4520205P	Nos x Sq.mm 5 x 2 x 0.22	Nos. 7	mm 0.21	mm 0.70	mm 6.50	mm 7.40	kg/km 63.5	Ω/km 84.8

✓ We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.



www.siechem.com