

Application

- ✓ Low-tension electric wire for Automobiles.
- ✓ Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.
- ✓ Especially used for circuits requiring heat resistance.

Product Construction

- ✓ Conductor : Bare copper conductor, (Symmetrical Structure A).
- ✓ Insulation : PP low halogenated. (Reduced Wall thickness).
- ✓ Colour : As per customer order.

Technical Data

- ✓ Temperature Range : -40°C to 125°C / 3000hrs.
- ✓ Voltage : 60V
- ✓ Min. Bending radius: 5 x Cable OD
- ✓ Standard : ES-AUST-1A348-AA-G, ISO 6722.
- ✓ A3 : 125°C
- ✓ 9Y : Polypropylene
- ✓ 3 : Temperature Class C
- ✓ T : Thin wall
- ✓ A : Structure A
- ✓ D : Bare copper


Features

- ✓ Flame retardant
- ✓ Highly resistant against acids, alkaline, petrol and diesel.
- ✓ Extra flexibility.
- ✓ RoHS.

Automotive Cables

A39Y - 3TAD

2D View




Approvals	Accreditations	Certifications

Part Number	Conductor Construction				Insulation Wall Thickness Min.	Cable			Max. Conductor Resistance at 20°C	Current carrying capacity	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire Max.	Conductor Diameter Max.		Overall Diameter		Weight Approx.			
						Min.	Max.				
	mm²	nos.	mm	mm	mm	mm	mm	kg/km	Ω/km	Amps	mtrs
D18705XX	0.35	7	0.27	0.90	0.20	1.20	1.40	4	54.4	12	500
D18705XX	0.50	19	0.19	1.10	0.22	1.40	1.60	5	37.1	15	500
D18708XX	0.75	19	0.24	1.30	0.24	1.70	1.90	8	24.7	19	500
D18710XX	1.00	19	0.27	1.50	0.24	1.90	2.10	10	18.5	24	500
D18713XX	1.50	19	0.33	1.80	0.24	2.20	2.40	15	12.7	30	500
D18714XX	2.00	19	0.38	2.00	0.28	2.50	2.80	20	9.42	37	500
D18716XX	2.50	37	0.28	2.20	0.28	2.70	3.00	25	7.60	42	500
D18717XX	3.00	37	0.34	2.40	0.32	3.10	3.40	30	6.15	49	500
D18719XX	4.00	37	0.38	2.80	0.32	3.40	3.70	40	4.71	58	500
D18721XX	5.00	37	0.43	3.10	0.32	3.90	4.20	49	3.94	66	500
D18723XX	6.00	37	0.45	3.40	0.32	4.00	4.30	58	3.14	75	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ * Other length as per Customer order.
- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 125°C and ambient temperature of 40°C.
- ✓ ** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.


www.siechem.com