

Application

- ✓ Low-tension electric wire for Automobiles.
- ✓ Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.

Features


- ✓ Electron Beam Cross Linked.
- ✓ Flame retardant.
- ✓ Highly resistant against acids, alkaline, petrol and diesel.
- ✓ Extra flexibility.
- ✓ RoHS.

Product Construction

- ✓ Conductor : Bare copper conductor.
- ✓ Insulation : EBXL-XLPE.
- ✓ Color : As per customer order.

**Automotive
Cables**
AEX

2D View



Technical Data

- ✓ Temperature Range : -40°C to 135°C / 3000hrs.
- ✓ Voltage : 60V
- ✓ Standard : ES91110-05, JASO D611:2014.

Approvals	Accreditations	Certifications

Part Number	Conductor Construction				Insulation Wall Thickness Min.	Cable Overall Diameter		Weight Approx.	Max. Conductor Resistance at 20°C	Current Carrying Capacity	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire Max.	Conductor Diameter Max.		Nom.	Max.				
	mm ²	nos.	mm	mm	mm	mm	mm	kg/km	Ω/km	Amps	mtrs
B52904XX	0.30	7	0.26	0.8	0.5	1.8	1.9	7	50.2	14	500
B52906XX	0.50	7	0.32	1.0	0.5	2.0	2.1	9	32.7	18	500
B52954XX	0.85	11	0.32	1.2	0.5	2.2	2.3	13	20.8	24	500
B52912XX	1.25	16	0.32	1.5	0.6	2.7	2.8	18	14.3	31	500
B52914XX	2.00	26	0.32	1.9	0.6	3.1	3.2	25	8.81	42	500
B52917XX	3.00	41	0.32	2.4	0.7	3.8	3.9	40	5.59	55	500
B52921XX	5.00	65	0.32	3.0	0.8	4.6	4.8	62	3.94	74	500
B52925XX	8.00	50	0.45	3.7	0.8	5.3	5.5	90	2.32	96	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ * Other length as per Customer order.
- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 135°C and ambient temperature of 40°C.
- ✓ ** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.


www.siechem.com