

Siechem ATC, 125°C Diesel Electric Locomotive Cables

Application

- ✓ Thin walled Flexible EBXL Cables for Tap Changer of Electric Locomotives.
- ✓ For Diesel Electric Locomotive Cables.

Product Construction

- ✓ Conductor : Annealed Tinned Copper Flexible Conductor.
- ✓ Insulation : Electron Beam Cross linked Specially Formulated Polyolefin
- ✓ Individual Shielding : ATC Min 95% Coverage
- ✓ Filler:Optional
- ✓ Tape : Polyester
- ✓ Outersheath : Electron Beam Cross Linked polyolefin
- ✓ Colour : Dark Grey.
- ✓ Marking : Siechem Part No. 260800 4CX16AWG 125°C 600V Year


Technical Data

- ✓ Temperature Range : -65°C to +125°C
- ✓ Voltage Grade : 600 V
- ✓ NFPA -130

Features


- ✓ Excellent resistance to high and low temperature
- ✓ Outstanding Flame retardant
- ✓ Excellent flexibility
- ✓ Resistance to Oil, Fuel, Ozone and Weathering.
- ✓ Easy to strip
- ✓ Very Low smoke density
- ✓ Soldering iron resistant
- ✓ Electron Beam Cross Linked.

2D View



Approvals	Accreditations	Certifications

**



Part Number	Number of Cores and Conductor Size	Outer Diameter in		Conductor Resistance at 20°C	Total Weight Kg/Km approx.
		mm	Inches		
2608004	4Cx16 AWG	11.94 ± 0.57	0.470± 0.02	15.81	223.13

** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.

