

Application

- ✓ Wire harness of low-tension electric circuits for automobiles.
- ✓ Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.
- ✓ Especially used for circuits requiring heat resistance.

Product Construction

- ✓ Conductor : Soft-annealed electrolytic copper E-Cu ETP1 according to JIS C3102, bare conductor construction according to JASO D 608
- ✓ Insulation : Electron beam cross linked PVC.
- ✓ Colour : As per customer order.
- ✓ Single core

Technical Data


- ✓ Temperature Range :
- 40°C to +100°C (3000 Hours)
- ✓ Standard : JASO D 608 : 2014
- ✓ Test Voltage : 1 kV
- ✓ A : Low tension cables for automobiles
- ✓ V : Vinyl insulated
- ✓ X : Cross linked
- ✓ f : Extra flexible Conductor

Features

- ✓ Flame retardant
- ✓ Highly resistant against acids, lyes, petrol and diesel.
- ✓ Extra flexible conductor with electron beam cross linked PVC thin wall insulation for smaller diameter and lesser weight.
- ✓ Excellent flexibility.
- ✓ Heat resistant.

Automotive Cables **AVX f**

2D View



Approvals	Accreditations	Certifications

Part Number	Conductor Construction				Insulation Wall Thickness Nom.	Cable			Max. Conductor Resistance at 20°C	Current Carrying Capacity	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire max.	Conductor Diameter Approx.		Overall Diameter		Weight Approx.			
						Nom.	Max.				
	mm ²	nos.	mm	mm	mm	mm	kg/km	Ω/km	Amps	mtrs	
81206XX*	0.5	20	0.18	1.0	0.5	2.0	2.2	8.71	36.7	14	1000
81208XX	0.75	30	0.18	1.2	0.5	2.2	2.4	12.96	24.4	18	1000
81212XX	1.25	50	0.18	1.5	0.5	2.7	2.9	61.0	14.7	25	1000

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ * Other length as per Customer order.
- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 100°C and ambient air temperature of 40°C.
- ** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.



www.siechem.com