



Siechem Annealed Tinned Copper Conductor Synthetic Elastomeric Insulated, Unsheathed Multi Core Rubber Cable as per IS 9968 Part-1

Application

- ✓ Used for measuring & controlling in control equipment for conveyors and control units
- ✓ Fixed installation and for flexible use when temporarily moved in medium mechanical condition
- ✓ Used outdoors when protected and in dry or moist conditions indoor.
- ✓ Suitable for many applications, including use in elevators, lifts, cranes, mines, heater leads, and electric iron leads etc.

Product Construction

- ✓ Conductor : Annealed Tinned Copper, Class 2 (Optional - Aluminium Conductor as per Customer requirement)
- ✓ Separator Tape (Optional)
- ✓ Insulation : Silicon Rubber, Type IE 5 as per IS 6380-1984
- ✓ Filling (optional)
- ✓ Braiding : Glass Fibre Yarn

Technical Data


- ✓ Temperature Range : Silicon Rubber Insulation : 150°C
- ✓ High Voltage Test : 3 kV for 5 mins
- ✓ Rated Voltage : 1.1 kV
- ✓ Specification : IS 9968 Part - 1

1st time in India
EBXL Rubber Cable
as per IS 9968
with enhanced properties

Features

- ✓ Flexible
- ✓ Abrasion Resistance
- ✓ High Dielectric Strength
- ✓ Flame Retardant
- ✓ Medium Mechanical Stress
- ✓ Long Cable life.

2D View



Approvals	Accreditations	Certifications

Part Number	No.of Cores X Conductor size (Nos X mm ²)	Thickness of Insulation (mm)	Outer Diameter (mm) approx.	Copper Index (Kg/Km)	Weight (Kg/Km) approx.
5211604	4C X 2.5	1.0	9.73	86.14	141.34
5211904	4C X 4	1.0	10.89	137.83	201.96
5212304	4C X 6	1.0	12.10	206.75	280.31
5212104	4C X 10	1.2	16.44	344.58	465.69
5212804	4C X 16	1.2	19.04	551.32	696.03
5213004	4C X 25	1.2	22.31	861.44	1035.82
5213204	4C X 35	1.4	26.10	1206.02	1440.24
5213404	4C X 50	1.6	30.13	1722.88	2028.54

** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.

