



Siechem Annealed Tinned Copper Conductor Synthetic Elastomeric Insulated, Unsheathed Multi Core Rubber Cable as per IS 9968 Part-1

Application

- ✓ Used for measuring & controlling in control equipment for conveyors and control units
- ✓ Fixed installation and for flexible use when temporarily moved in medium mechanical condition
- ✓ Used outdoors when protected and in dry or moist conditions indoor.
- ✓ Suitable for many applications, including use in elevators, lifts, cranes, mines, heater leads, and electric iron leads etc.

Features

- ✓ Flexible
- ✓ Abrasion Resistance
- ✓ High Dielectric Strength
- ✓ Flame Retardant
- ✓ Medium Mechanical Stress
- ✓ Long Cable life.

Product Construction


- ✓ Conductor : Annealed Tinned Copper, Class 2 (Optional - Aluminium Conductor as per Customer requirement)
- ✓ Separator Tape (Optional)
- ✓ Insulation : Silicon Rubber, Type IE 5 as per IS 6380-1984
- ✓ Filling (optional)
- ✓ Braiding : Glass Fibre Yarn

Technical Data

- ✓ Temperature Range : Silicon Rubber Insulation : 150°C
- ✓ High Voltage Test : 3 kV for 5 mins
- ✓ Rated Voltage : 1.1 kV
- ✓ Specification : IS 9968 Part - 1

1st time in India
EBXL Rubber Cable
as per IS 9968
with enhanced properties

2D View



Approvals	Accreditations	Certifications

**

Part Number	No. of Cores X Conductor size (Nos X mm ²)	Thickness of Insulation (mm)	Outer Diameter (mm) approx.	Copper Index (Kg/Km)	Weight (Kg/Km) approx.
5211602	2C X 2.5	1.0	8.07	43.07	72.16
5211902	2C X 4	1.0	9.02	68.92	102.65
5212302	2C X 6	1.0	10.02	103.37	142.01
5212702	2C X 10	1.2	13.61	172.29	235.37
5212802	2C X 16	1.2	15.75	275.66	350.94
5213002	2C X 25	1.2	18.46	430.72	521.34
5213202	2C X 35	1.4	21.59	603.01	724.13
5213402	2C X 50	1.6	24.92	861.44	1018.90

** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.

