

Application

- ✓ Low-tension electric wire for Automobiles.
- ✓ Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.
- ✓ Especially used for circuits requiring heat resistance.

Features

- ✓ Flame retardant.
- ✓ Highly resistant against acids, alkaline, petrol and diesel.
- ✓ Extra flexibility.
- ✓ Electron Beam Cross Linked.
- ✓ RoHS.

Product Construction

- ✓ Conductor : Bare copper conductor, (Symmetrical structure A)
- ✓ Insulation : EBXL - XLPE, (Decreased wall thickness).
- ✓ Color : As per customer order.


Technical Data

- ✓ Temperature Range : -40°C to 150°C / 3000hrs.
- ✓ Voltage : 60V.
- ✓ Standard : B25 1110.

Automotive
Cables

C4ZH

2D View



Approvals	Accreditations	Certifications
	**	

Part Number	Conductor Construction				Insulation Wall Thickness Min.	Cable Overall Diameter		Weight Approx.	Max. Conductor Resistance at 20°C	Current Carrying Capacity	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire Max.	Conductor Diameter Max.		Min.	Max.				
	mm ²	nos.	mm	mm	mm	mm	mm	kg/km	Ω/km	Amps	mtrs
D20805XX	0.35	7	0.27	0.9	0.20	1.25	1.35	5	54.4	13	500
D20806XX	0.50	19	0.19	1.1	0.20	1.40	1.60	7	37.1	18	500
D20808XX	0.75	19	0.24	1.3	0.20	1.60	1.80	10	24.7	23	500
D20810XX	1.00	19	0.27	1.5	0.25	1.75	1.95	13	18.5	28	500
D20812XX	1.25	19	0.30	1.7	0.25	2.00	2.20	15	14.9	32	500
D20813XX	1.50	19	0.33	1.8	0.25	2.10	2.25	18	12.7	35	500
D20814XX	2.00	37	0.38	2.0	0.25	2.30	2.50	24	9.42	42	500
D20816XX	2.50	37	0.28	2.2	0.30	2.70	2.90	28	7.60	49	500
D20817XX	3.00	37	0.34	2.4	0.30	3.00	3.20	43	6.15	56	500
D20819XX	4.00	37	0.38	2.8	0.30	3.40	3.70	65	4.71	66	500
D20821XX	5.00	37	0.43	3.1	0.30	3.70	3.90	101	3.94	75	500
D20823XX	6.00	37	0.45	3.4	0.35	4.10	4.30	132	3.14	85	500
D20825XX	8.00	98	0.33	4.3	0.35	4.60	4.80	199	2.38	103	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ * Other length as per Customer order.
- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 150°C and ambient temperature of 40°C.
- ✓ ** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.



www.siechem.com