

Siechem EMD/40019324 ATC, 125°C Diesel Electric Locomotive Cables

Application

- ✓ Thin walled Flexible EBXL Cables for Tap Changer of Electric Locomotives.
- ✓ For Diesel Electric Locomotive Cables.

Product Construction

- ✓ Conductor : Annealed Tinned Copper Flexible Conductor.
- ✓ Insulation : Specially formulated Dual Layer, EBXL 125°C
- ✓ Braiding
- ✓ Tape : Polyester
- ✓ Inner shield : Cu.Mylar Tape
- ✓ Drain wire : ATC
- ✓ Outer shield : ATC
- ✓ Outersheath : Specially formulated Dual Layer, EBXL 125°C
- ✓ Colour : Grey or as per Customer order.


Technical Data

- ✓ Temperature Range : -55°C to +125°C (>10000 hrs @ +125°C).
- ✓ Rated Voltage : 250 V DC
- ✓ Specification: EDPS 179 - 40019324
- ✓ NFPA - 130

Features

- ✓ Excellent resistance to high and low temperature
- ✓ Outstanding Flame retardant
- ✓ Halogen free
- ✓ Excellent flexibility
- ✓ Resistance to Oil, Fuel, Ozone and Weathering.
- ✓ Easy to strip
- ✓ Low smoke density
- ✓ Soldering iron resistant
- ✓ Electron Beam Cross Linked.

2D View



Approvals	Accreditations	Certifications

**



EMD Part Number	Number of Cores and Conductor Size	Outer Diameter in		Total Weight Kg/Km approx.
		mm	Inches	
40019324	2Cx20 AWG	6.1976+152/6.1976-0.381	0.244+0.006/0.244-0.015	73.19

** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.



www.siechem.com