

Siechem EMD/40036047 ATC, 125°C Diesel Electric Locomotive Cables

Application

- ✓ Thin walled flexible EBXL cables for tap changer of Electric Locomotives.
- ✓ For Diesel Electric Locomotive Cables.

Product Construction

- ✓ Conductor : Annealed Tinned Copper Flexible Conductor.
- ✓ Insulation : Specially formulated Dual Layer, EBXL125°C.
- ✓ Laid up : Cores are twisted.
- ✓ Colour : Yellow/Brown, Yellow/Red, Yellow/Orange or as per Customer order.


Technical Data

- ✓ Temperature Range : -65°C to +125°C (>10000 hrs @ +125°C).
- ✓ Rated Voltage : 600 V AC
- ✓ Specification: EDPS 179 - 40036047
- ✓ NFPA -130

Features


- ✓ Excellent resistance to high and low temperature
- ✓ Outstanding flame retardant
- ✓ Halogen free
- ✓ Excellent flexibility
- ✓ Resistance to Oil, Fuel, Ozone and Weathering.
- ✓ Easy to strip
- ✓ Low smoke density
- ✓ Soldering iron resistant
- ✓ Electron Beam Cross Linked.

2D View



Approvals	Accreditations	Certifications

**



EMD Part Number	Number of Cores and Conductor Size	Outer Diameter (Nom)		Total Weight Kg/Km approx.
		mm	Inches	
40036047	3Cx18 AWG	5.84	0.230	49.94

** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.