

Application

- ✓ Low-tension electric wire for Automobiles.
- ✓ Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.
- ✓ Especially used for circuits requiring heat resistance.

Features

- ✓ Flame retardant
- ✓ Highly resistant against acids, alkaline, petrol and diesel.
- ✓ Extra flexibility.
- ✓ Electron beam cross linked.
- ✓ RoHS

Product Construction

- ✓ Conductor : Bare copper conductor, (Asymmetrical Structure C).
- ✓ Insulation : EBXL - XLPO Zero halogen, Flame retardant. (Thick wall)


Technical Data

- ✓ Temperature Range : -40°C to 125°C / 3000hrs
- ✓ Voltage : 60V
- ✓ Min. bending radius : 5xCable OD
- ✓ Standard: ISO 19642-3
MBN LV 112-1 (Class C)

Automotive
Cables

FL2X - C

2D View



Approvals	Accreditations	Certifications

Part Number	Conductor Construction				Insulation Wall Thickness Min.	Cable Overall Diameter		Weight Approx.	Max. Conductor Resistance at 20°C	Current Carrying Capacity	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire Max.	Conductor Diameter Max.		Min.	Max.				
	mm ²	nos.	mm	mm	mm	mm	mm	kg/km	Ω/km	Amps	mtrs
D21925XX	8.00	240	0.21	4.30	0.64	5.00	5.90	83	2.38	88	500
D21927XX	10.00	320	0.21	4.50	0.80	5.90	6.50	105	1.82	109	500
D219A11XX	12.00	380	0.21	5.40	0.80	6.60	7.40	120	1.52	120	500
D21928XX	16.00	512	0.21	6.30	0.80	7.70	8.30	163	1.16	147	500
D21930XX	25.00	790	0.21	7.80	1.04	9.40	10.40	280	0.743	193	500
D21932XX	35.00	1070	0.21	9.00	1.04	9.60	11.60	343	0.527	236	500
D21934XX	50.00	1600	0.21	10.50	1.20	11.50	13.50	491	0.368	291	500
D21937XX	70.00	1427	0.26	12.50	1.20	13.50	15.50	700	0.259	359	500
D21938XX	95.00	1936	0.26	14.80	1.28	16.00	18.00	950	0.196	428	500
D21941XX	120.00	2450	0.26	16.50	1.28	17.70	19.70	1200	0.153	509	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ * Other length as per Customer order.
- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 125°C and ambient temperature of 40°C.
- ✓ ** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.



www.siechem.com