

**Application**

- ✓ Low-tension electric wire for Automobiles.
- ✓ Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.
- ✓ Especially used for circuits requiring heat resistance.

**Product Construction**

- ✓ Conductor : Stranded copper alloy.
- ✓ Insulation : EBXL-XLPE.  
(Reduced wall thickness).
- ✓ Colour : As per customer order.

**Technical Data**


- ✓ Temperature Range : -40°C to 125°C / 3000hrs.
- ✓ Voltage : 60V.
- ✓ Min. Bending radius : 5 x Cable OD.
- ✓ FL : Automotive Cable.
- ✓ CuSn03 : Copper alloys.
- ✓ R : Reduced wall thickness.
- ✓ 2X : PE-X (Polyethylene cross linked).
- ✓ Standard : ISO 19642-3.

**Features**

- ✓ Electron Beam Cross Linked.
- ✓ Flame retardant.
- ✓ Highly resistant against acids, alkaline, petrol and diesel.
- ✓ Extra flexibility.
- ✓ Light weight
- ✓ Excellent resistance to oil and flame.
- ✓ RoHS.

Automotive  
Cables

## FLCuSn03R2X T3

**2D View**

Approvals	Accreditations	Certifications
		**

Part Number	Conductor Construction				Insulation Wall Thickness Min.	Cable			Max. Conductor Resistance at 20°C	Current Carrying Capacity	Standard Length*				
	Nominal Cross-Section	No. of Strands	Diameter of Single wire Max.	Conductor Diameter Max.		Core Diameter		Weight Approx.							
						Min.	Max.								
	mm <sup>2</sup>	nos.	mm	mm	mm	mm	mm	kg/km	Ω/km	Amps	mtrs				
D22801XX	0.13	7	0.16	0.5	0.20	0.95	1.05	2	170	6	500				

Note : XX\* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

✓ \* Other length as per Customer order.

✓ Current Carrying capacity given is for the maximum conductor operating temperature of 125°C and ambient temperature of 40°C.

\*\* We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.



[www.siechem.com](http://www.siechem.com)